

This listing of claims will replace all prior versions, and listings, of claims in the application. Please cancel claims 1 and 11, without prejudice or disclaimer, and amend claim 12 as follows:

1. (Canceled)
2. (Previously Amended) A wellbore casing, comprising:  
a tubular member including at least one thin wall section at an end of the tubular member and a thick wall section adjacent to the thin wall section; and  
a compressible annular member coupled to each thin wall section.
3. (Canceled)
4. (Previously Amended) A wellbore casing, comprising:  
a first tubular member having a first inside diameter; and  
a second tubular member having a second inside diameter equal to the first inside diameter coupled to the first tubular member in an overlapping relationship;  
wherein the first and second tubular members are coupled by the process of deforming a portion of the second tubular member into contact with a portion of the first tubular member.
5. (Canceled)
6. (Previously Amended) An apparatus, comprising:  
one or more solid tubular members, each solid tubular member including one or more external seals;  
one or more perforated tubular members coupled to the solid tubular members;  
and  
a shoe coupled to one of the perforated tubular members;

wherein a portion of at least one of the solid tubular members overlap with a portion of at least one of the perforated tubular members; and wherein the inside diameters of the non-overlapping portions of the overlapping solid and perforated tubular members are equal.

7. (Canceled)

8. (Previously Amended) An apparatus, comprising:  
one or more primary solid tubulars, each primary solid tubular including one or more external annular seals;  
n perforated tubulars coupled to the primary solid tubulars;  
n-1 intermediate tubulars coupled to and interleaved among the perforated tubulars, each intermediate tubular including one or more external annular seals; and  
a shoe coupled to one of the perforated tubulars;  
wherein a portion of at least one of the primary solid tubulars overlap with a portion of at least one of the perforated tubulars; and  
wherein the inside diameters of the non-overlapping portions of the overlapping primary solid and perforated tubulars are equal.

9. (Canceled)

10. (Canceled)

11. (Canceled)

12. (Currently Amended) A wellbore casing, comprising:  
a first tubular member; and  
a second tubular member coupled to the first tubular member in an overlapping relationship;  
wherein an inner diameter of the first tubular member is equal to an inner

diameter of the second tubular member; [The wellbore casing of claim 1,]  
wherein a portion of the first tubular member overlaps with a portion of the  
second tubular member;  
wherein the portion of the first tubular member that overlaps with the portion of  
the second tubular member comprises a thin walled portion; and  
wherein the portion of the first tubular member that does not overlap with the  
portion of the second tubular member comprises a thick walled portion.

13. (Previously Presented) The wellbore casing of claim 12, wherein the thin walled portion of the first tubular member comprises a compressible annular sealing member.

14. (Previously Presented) The wellbore casing of claim 12, wherein the portion of the second tubular member that overlaps with the portion of the first tubular member comprises a thin walled portion; and wherein the portion of the second tubular member that does not overlap with the portion of the first tubular member comprises a thick walled portion.

15. (Previously Presented) The wellbore casing of claim 14, wherein the thin walled portion of the second tubular member comprises a compressible annular sealing member.

16. (Previously Presented) The wellbore casing of claim 2, wherein the compressible annular member is coupled to an exterior surface of the thin wall section of the tubular member.

17. (Previously Presented) The wellbore casing of claim 2, wherein the thin wall section of the tubular member is plastically deformed.

18. (Previously Presented) The wellbore casing of claim 4, wherein a portion of the first tubular member overlaps with a portion of the second tubular member; wherein

the portion of the first tubular member that overlaps with the portion of the second tubular member comprises a thin walled portion; and wherein the portion of the first tubular member that does not overlap with the portion of the second tubular member comprises a thick walled portion.

19. (Previously Presented) The wellbore casing of claim 18, wherein the thin walled portion of the first tubular member comprises a compressible annular sealing member.

20. (Previously Presented) The wellbore casing of claim 18, wherein the portion of the second tubular member that overlaps with the portion of the first tubular member comprises a thin walled portion; and wherein the portion of the second tubular member that does not overlap with the portion of the first tubular member comprises a thick walled portion.

21. (Previously Presented) The wellbore casing of claim 20, wherein the thin walled portion of the second tubular member comprises a compressible annular sealing member.

22. (Previously Presented) The apparatus of claim 6, wherein the overlapping portion of the at least one solid tubular member comprises a thin walled portion; and wherein non-overlapping portion of the at least one solid tubular member comprises a thick walled portion.

23. (Previously Presented) The apparatus of claim 22, wherein the thin walled portion of the at least one solid tubular member comprises a compressible annular sealing member.

24. (Previously Presented) The apparatus of claim 22, wherein the overlapping portion of the at least one perforated tubular member comprises a thin walled portion;

and wherein the non-overlapping portion of the at least one perforated tubular member comprises a thick walled portion.

25. (Previously Presented) The apparatus of claim 24, wherein the thin walled portion of the at least one perforated tubular member comprises a compressible annular sealing member.

26. (Previously Presented) The apparatus of claim 6, wherein the overlapping portion of the at least one perforated tubular member comprises a thin walled portion; and wherein the non-overlapping portion of the at least one perforated tubular member comprises a thick walled portion.

27. (Previously Presented) The apparatus of claim 26, wherein the thin walled portion of the at least one perforated tubular member comprises a compressible annular sealing member.

28. (Previously Presented) The apparatus of claim 8, wherein the overlapping portion of the at least one primary solid tubular comprises a thin walled portion; and wherein the non-overlapping portion of the at least one primary solid tubular comprises a thick walled portion.

29. (Previously Presented) The apparatus of claim 28, wherein the thin walled portion of the at least one primary solid tubular comprises a compressible annular sealing member.

30. (Previously Presented) The apparatus of claim 28, wherein the overlapping portion of the at least one perforated tubular comprises a thin walled portion; and wherein the non-overlapping portion of the at least one perforated tubular member a thick walled portion.

31. (Previously Presented) The apparatus of claim 30, wherein the thin walled

portion of the at least one perforated tubular comprises a compressible annular sealing member.

32. (Previously Presented) The apparatus of claim 8, wherein the overlapping portion of the at least one perforated tubular comprises a thin walled portion; and wherein the non-overlapping portion of the at least one perforated tubular comprises a thick walled portion.

33. (Previously Presented) The apparatus of claim 32, wherein the thin walled portion of the at least one perforated tubular comprises a compressible annular sealing member.

34. (Previously Presented) A wellbore casing, comprising:  
a first tubular member; and  
a second tubular member coupled to the first tubular member in an overlapping relationship;  
wherein a portion of the first tubular member overlaps with a portion of the second tubular member;  
wherein the portion of the first tubular member that overlaps with the portion of the second tubular member comprises a thin walled portion;  
wherein the thin walled portion of the first tubular member comprises a compressible annular sealing member;  
wherein the portion of the first tubular member that does not overlap with the portion of the second tubular member comprises a thick walled portion;  
wherein the portion of the second tubular member that overlaps with the portion of the first tubular member comprises a thin walled portion;  
wherein the thin walled portion of the second tubular member comprises a compressible annular sealing member;  
wherein the portion of the second tubular member that does not overlap with the portion of the first tubular member comprises a thick walled portion; and

wherein an inner diameter of the non-overlapping portion of the first tubular member is equal to an inner diameter of the non-overlapping portion of the second tubular member.

35. (Previously Presented) A wellbore casing, comprising:  
a first tubular member; and  
a second tubular member coupled to the first tubular member in an overlapping relationship;  
wherein a portion of the first tubular member overlaps with a portion of the second tubular member;  
wherein the portion of the first tubular member that overlaps with the portion of the second tubular member comprises a thin walled portion;  
wherein the thin walled portion of the first tubular member comprises a compressible annular sealing member;  
wherein the portion of the first tubular member that does not overlap with the portion of the second tubular member comprises a thick walled portion;  
wherein the portion of the second tubular member that overlaps with the portion of the first tubular member comprises a thin walled portion;  
wherein the thin walled portion of the second tubular member comprises a compressible annular sealing member; and  
wherein the portion of the second tubular member that does not overlap with the portion of the first tubular member comprises a thick walled portion.
36. (Previously Presented) A wellbore casing, comprising:  
a first tubular member having a first inside diameter; and  
a second tubular member having a second inside diameter equal to the first inside diameter coupled to the first tubular member in an overlapping relationship;  
wherein the first and second tubular members are coupled by the process of deforming a portion of the second tubular member into contact with a portion of the first tubular member;

wherein a portion of the first tubular member overlaps with a portion of the second tubular member;

wherein the portion of the first tubular member that overlaps with the portion of the second tubular member comprises a thin walled portion;

wherein the thin walled portion of the first tubular member comprises a compressible annular sealing member;

wherein the portion of the first tubular member that does not overlap with the portion of the second tubular member comprises a thick walled portion;

wherein the portion of the second tubular member that overlaps with the portion of the first tubular member comprises a thin walled portion;

wherein the thin walled portion of the second tubular member comprises a compressible annular sealing member;

wherein the portion of the second tubular member that does not overlap with the portion of the first tubular member comprises a thick walled portion; and

wherein an inner diameter of the non-overlapping portion of the first tubular member is equal to an inner diameter of the non-overlapping portion of the second tubular member.

37. (Previously Presented) A wellbore casing, comprising:
- a first tubular member having a first inside diameter; and
- a second tubular member having a second inside diameter equal to the first inside diameter coupled to the first tubular member in an overlapping relationship;
- wherein the first and second tubular members are coupled by the process of deforming a portion of the second tubular member into contact with a portion of the first tubular member;
- wherein a portion of the first tubular member overlaps with a portion of the second tubular member;
- wherein the portion of the first tubular member that overlaps with the portion of the second tubular member comprises a thin walled portion;
- wherein the thin walled portion of the first tubular member comprises a



compressible annular sealing member;  
wherein the portion of the first tubular member that does not overlap with the  
portion of the second tubular member comprises a thick walled portion;  
wherein the portion of the second tubular member that overlaps with the portion  
of the first tubular member comprises a thin walled portion;  
wherein the thin walled portion of the second tubular member comprises a  
compressible annular sealing member; and  
wherein the portion of the second tubular member that does not overlap with the  
portion of the first tubular member comprises a thick walled portion.

38. (Previously Presented) An apparatus, comprising:  
one or more solid tubular members, each solid tubular member including one or  
more external seals;  
one or more perforated tubular members coupled to the solid tubular members;  
and  
a shoe coupled to one of the perforated tubular members;  
wherein a portion of at least one of the solid tubular members overlap with a  
portion of at least one of the perforated tubular members; and  
wherein the overlapping portion of the at least one solid tubular member  
comprises a thin walled portion;  
wherein the thin walled portion of the at least one solid tubular member  
comprises a compressible annular sealing member;  
wherein non-overlapping portion of the at least one solid tubular member  
comprises a thick walled portion;  
wherein the overlapping portion of the at least one perforated tubular member  
comprises a thin walled portion;  
wherein the thin walled portion of the at least one perforated tubular member  
comprises a compressible annular sealing member;  
wherein the non-overlapping portion of the at least one perforated tubular  
member comprises a thick walled portion; and  
wherein an inner diameter of the non-overlapping portion of the at least one solid

tubular member is equal to an inner diameter of the at least one perforated tubular member.

39. (Previously Presented) An apparatus, comprising:  
one or more solid tubular members, each solid tubular member including one or more external seals;  
one or more perforated tubular members coupled to the solid tubular members;  
and  
a shoe coupled to one of the perforated tubular members;  
wherein a portion of at least one of the solid tubular members overlap with a portion of at least one of the perforated tubular members; and  
wherein the overlapping portion of the at least one solid tubular member comprises a thin walled portion;  
wherein the thin walled portion of the at least one solid tubular member comprises a compressible annular sealing member;  
wherein non-overlapping portion of the at least one solid tubular member comprises a thick walled portion;  
wherein the overlapping portion of the at least one perforated tubular member comprises a thin walled portion;  
wherein the thin walled portion of the at least one perforated tubular member comprises a compressible annular sealing member; and  
wherein the non-overlapping portion of the at least one perforated tubular member comprises a thick walled portion.
40. (Previously Presented) An apparatus, comprising:  
one or more primary solid tubular members, each primary solid tubular member including one or more external annular seals;  
n perforated tubular members coupled to the primary solid tubular members;  
n-1 intermediate tubular members coupled to and interleaved among the perforated tubular members, each intermediate tubular member including one or more external annular seals; and

a shoe coupled to one of the perforated tubular members;  
wherein a portion of at least one of the primary solid tubular members overlap  
with a portion of at least one of the perforated tubular members;  
wherein the overlapping portion of the at least one primary solid tubular member  
comprises a thin walled portion;  
wherein the thin walled portion of the at least one primary solid tubular member  
comprises a compressible annular sealing member;  
wherein the non-overlapping portion of the at least one primary solid tubular  
member comprises a thick walled portion;  
wherein the overlapping portion of the at least one perforated tubular member  
comprises a thin walled portion;  
wherein the thin walled portion of the at least one perforated tubular member  
comprises a compressible annular sealing member;  
wherein the non-overlapping portion of the at least one perforated tubular  
member comprises a thick walled portion; and  
wherein an inner diameter of the non-overlapping portion of the at least one  
primary solid tubular member is equal to an inner diameter of the at least  
one perforated tubular member.

41. (Previously Presented) An apparatus, comprising:  
one or more primary solid tubular members, each primary solid tubular member  
including one or more external annular seals;  
n perforated tubular members coupled to the primary solid tubular members;  
n-1 intermediate tubular members coupled to and interleaved among the  
perforated tubular members, each intermediate tubular member including  
one or more external annular seals; and  
a shoe coupled to one of the perforated tubular members;  
wherein a portion of at least one of the primary solid tubular members overlap  
with a portion of at least one of the perforated tubular members;  
wherein the overlapping portion of the at least one primary solid tubular member  
comprises a thin walled portion;

wherein the thin walled portion of the at least one primary solid tubular member comprises a compressible annular sealing member;  
wherein the non-overlapping portion of the at least one primary solid tubular member comprises a thick walled portion;  
wherein the overlapping portion of the at least one perforated tubular member comprises a thin walled portion;  
wherein the thin walled portion of the at least one perforated tubular member comprises a compressible annular sealing member; and  
wherein the non-overlapping portion of the at least one perforated tubular member comprises a thick walled portion.